

Technical Information: ULF MORITZ Scala

as of June 15

1. Description

SCALA stands for sensual Opulence. The collection offers highest refinement in the selection of materials: lacquer, glimmer, and as a true novum glass beads, which lend an exciting soft luster to the wallcoverings.

2. Material

Wallcoverings made by marburg wallcoverings are compliant with DIN EN 233. The basis is an non-woven substrate consisting of cellulose, textile fibers and a polymere binder. The colors used are manufactured on vinyl as well as water basis.

3. Roll Size

10,05 m x 0,75 m

4. Properties / Product Advantages

- conform with CE EN DIN 15102
- flame resistant EN DIN 13501-1
- highly washable DIN EN 233
- good lightfastness DIN EN 233
- dimensionally stable
- FSC®-certified base material
- eudermic material (no glass fiber)
- completely strippable when dry
- no heavy metals, no formaldehyde
- RAL-tested quality
- Ü-sign tested as per AgBB

5. Surface Requirements

Scala wallcoverings may be professionally installed on all interior plasters, gypsum or gypsumfiber boards, concrete suitable for wallpapering, as well as all carpentry and plywood boards. The surface must be smooth, clean, dry, evenly absorbant and supportive. It must have a neutral Ph value. Old wallcoverings and paints must be removed. Highly absorbant, chalky or sandy surfaces must be primed using a clear waterbased wallpapering primer. The surface must remain absorbant. Color differences in the surface must be primed with a white wallpapering primer.

Installing a Patent Vlies liner, article no. 9769 or 9792 yields an even surface, perfectly suited for wallpapering. After installation Patent Vlies liner must be preprepared with a diluted glue to regulate the absorbtion rate. Scala may be installed after approx. two hours drying time.

6. Glue & Application

Metylan NP Power Granulat plus and Pufas Security glue, as well as any other quality glue suitable for non -woven wallcoverings are suitable for hanging. Areas with high exposure may be hung using Metylan NP Power Granulat plus. Apply the glue evenly and not too thick directly to the wall with a short nap roller, working continuously by lengths. Cut the lengths with some overage and loosely fold backside out. Hang the length plumb into the glue bed, press on bubble - free using a wallpaper brush or soft rubber roller. Trim excess at ceilings, floors and windows using a sharp cutting knife and wallpaper spatula. Lightly press on seams using a conical seam roller



Apply Metylan seam and repair glue when overlapping in corners for example. Wallcovering corner strips on outside corners and window jambs allow for a perfect finish and change or pattern or colors.

CRUSH wallcoverings, item 74844 – 74850, 74877 – 74882: paste the wallcovering and book for 4 to 7 minutes.

Acrylic beads wallcoverings, item 74821 – 74824, 74858 – 74876: Brush off any loose beads from the back, avoid bringing the backside into contact with front and hang using the paste the wall technique.

ORIO wallcoverings, item 74801 – 74820: Excess glue may cause stains on the the tixtile fiber surface and must be avoided.

Es sind keine Weichzeiten zu beachten. Installers should wear fabric gloves to avoid stains by sweaty hands.

Attention: Hang lengths in same direction.

7. Care

Remove excess glue immediatly using clean water and a clean sponge. Dab off excess moisture with a clean cloth..

8. Installation Conditions

Avoid excessive heating or drafty conditions while the wallcoverings dry. Appropriate conditions are +15°C to +25°C and a relative indoor humidity of 30% to 60%.

9. Waste disposal

Scala wallcoverings may be discarded with the regular residential refuse.

Technical Advice

It is not possible to cover all possible aspects of any surface encountered in a given wallpaper hanging job in this leaflet. In the event that surfaces not mentioned in this leaflet are to be wallpapered, please consult us directly. The norms and technical guidelines for wallpaper hangers in Germany apply. The contents of this leaflet becomes obsolete with the publishing of a revised version. Do you have any quetions? We are glad to assist you - detailed and project specific.

Technical Consultation

MARBURGER TAPETENFABRIK
J. B. Schaefer GmbH & Co. KG
Bertram-Schaefer-Straße 11
35274 Kirchhain
Tel: 06422 81-162 oder -133
Fax: 06422 81-301
e-mail: service@marburg.com
Internet: www.marburg.com